



Rod ends GIKR22-PW (Series GIKR..-PW)

with internal thread, maintenance-free, to DIN ISO 12240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	22 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,021 / 0
d2	54 mm	
l4	111 mm	
	0 - 0,035 mm	Radial internal clearance
B	28 mm	Tolerance: 0 / -0,12
C1	20 mm	
D	42 mm	
d1	25,8 mm	
d3	M22X1,5	
d4	30 mm	
d5	38 mm	
dk	38,1 mm	
h1	84 mm	
l3	37 mm	
l5	12 mm	
l7	29 mm	
r1s min	0,3 mm	Chamfer dimension
W	32 mm	
α	15 °	
m	0,54 kg	Mass
Cr	68600 N	Basic dynamic load rating, radial
Cor	61100 N	Basic static load rating, radial

Basic load rating of housing

