



## Take-up housing units PHUSE50-XL-N (Series PHUSE)

cast iron and sheet steel housing, radial insert ball bearing with eccentric locking collar, P seals

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system ([https://www.schaeffler.de/content.schaeffler.de/en/news\\_media/index.jsp](https://www.schaeffler.de/content.schaeffler.de/en/news_media/index.jsp)) or by telephone on +49 (91 32) 82 - 28 97.

d	50 mm
H	130 mm
A	36 mm
A2	30 mm
B1	43,8 mm
d <sub>3 max</sub>	69 mm
F	20 mm
G	80 mm
H1	60 mm
J	180 mm
J1	100 mm

K <sub>1</sub>	M16	
L	256 mm	
L <sub>1</sub>	60 mm	
N	14 mm	
Q	M6	
S	4 mm	
S <sub>1</sub>	32,8 mm	
V	120 mm	
m	5,25 kg	Mass
C <sub>0r G</sub>	23200 N	Load carrying capacity of housing, radial
C <sub>r</sub>	37500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	23200 N	Basic static load rating, radial
	HUE10 / HUSE10	Designation of housing
	GRAE50-XL-NPP-B	Designation of bearing
	KASK10	Bearing end cap, closed design. To be ordered separately.
		Slot for bearing end cap

