



Rod ends GIKSR10-PS (Series GIKSR..-PS)

with internal thread, made from special steel,
maintenance-free, to DIN ISO 12 240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	10 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,015 / 0
d2 max	29 mm	
l4	57,5 mm	
	0,005 - 0,040 mm	Radial internal clearance
B	14 mm	Tolerance: 0 / -0,12
C1	10,5 mm	
D	22 mm	
d1	12,9 mm	
d3	M10	
d4	15 mm	
d5	19 mm	
dk	19 mm	
h1	43 mm	
l3 min	15 mm	
l5	6,5 mm	
l7 min	14 mm	
r1s min	0,3 mm	Chamfer dimension
W	17 mm	
α	13 °	
m	0,072 kg	Mass

Cr	18000 N	Basic dynamic load rating, radial
Cor	8000 N	Basic static load rating, radial Basic load rating of housing

