



## Spindle bearings

### B71908-E-2RSD-T-P4S (Series B719..-E-2RSD)

adjusted, in pairs or sets, contact angle  $\alpha = 25^\circ$ , lip seals  
on both sides, non-contact, restricted tolerances

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

|            |                                                   |
|------------|---------------------------------------------------|
| d          | 40 mm                                             |
| D          | 62 mm                                             |
| B          | 12 mm                                             |
| a          | 18 mm                                             |
| Da         | 58,5 mm Tolerance: H12                            |
| da         | 45 mm Tolerance: h12                              |
| r1<br>min  | 0,6 mm                                            |
| ra1<br>max | 0,6 mm                                            |
| ra<br>max  | 0,6 mm                                            |
| rmin       | 0,6 mm                                            |
| $\alpha$   | 25 ° Contact angle                                |
| m          | 0,103 kg Mass                                     |
| Cr         | 17100 N Basic dynamic load rating, radial         |
| C0r        | 9400 N Basic static load rating, radial           |
| ng<br>Fett | 20000 1/min Limiting speed for grease lubrication |
| Cur        | 970 N Fatigue limit load, radial                  |



