



## Rod ends GIKL16-PW (Series GIKL..-PW)

with internal thread, maintenance-free, to DIN ISO 12240-4, left hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	16 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,018 / 0
d2	42 mm	
l4	85 mm	
	0 - 0,035 mm	Radial internal clearance
B	21 mm	Tolerance: 0 / -0,12
C1	15 mm	
D	32 mm	
d1	19,3 mm	
d3	M16	
d4	22 mm	
d5	28 mm	
dk	28,575 mm	
h1	64 mm	
l3	28 mm	
l5	8 mm	
l7	23 mm	
r1s min	0,3 mm	Chamfer dimension
W	22 mm	
$\alpha$	15 °	
m	0,22 kg	Mass
C <sub>r</sub>	39000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	45200 N	Basic static load rating, radial

Basic load rating of housing

