



Rod ends GIKL6-PW (Series GIKL..-PW)

with internal thread, maintenance-free, to DIN ISO 12240-4, left hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

| | | |
|------------|--------------|---|
| d | 6 mm | Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,012 / 0 |
| d2 | 20 mm | |
| l4 | 40 mm | |
| | 0 - 0,035 mm | Radial internal clearance |
| B | 9 mm | Tolerance: 0 / -0,12 |
| C1 | 6,75 mm | |
| D | 16 mm | |
| d1 | 8,9 mm | |
| d3 | M6 | |
| d4 | 10 mm | |
| d5 | 13 mm | |
| dk | 12,7 mm | |
| h1 | 30 mm | |
| l3 | 12 mm | |
| l5 | 5 mm | |
| l7 | 11 mm | |
| r1s min | 0,3 mm | Chamfer dimension |
| W | 11 mm | |
| α | 13 ° | |
| | | Also corresponds to ISO 8139 |
| m | 0,022 kg | Mass |
| Cr | 7650 N | Basic dynamic load rating, radial |

Cor 8000 N Basic static load rating, radial
Basic load rating of housing

