



# Axial angular contact ball bearings

## ZKLF40115-2RS (Series ZKLF..-2RS)

double direction, for screw mounting, lip seals on both sides

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	40 mm	Tolerance: -0,005
D	115 mm	Tolerance: -0,01
B	46 mm	Tolerance: -0,25
	M6	Threaded connector for lubrication
	60 °	Contact angle
1)		Extraction slot
b	3 mm	
d1	65 mm	
d2	8,8 mm	
Da	80 mm	
max		
da	56 mm	
min		
l	36 mm	
J	94 mm	
r1	0,6 mm	
min		
rmin	0,6 mm	
t	12 X 30°	Pitch t Quantity X t
		Heavy series
m	2,2 kg	Mass

Ca	72000 N	Basic dynamic load rating, axial
Coa	149000 N	Basic static load rating, axial
n <sub>G</sub>	1600 1/min	Limiting speed for grease lubrication
Fett		
MRL	1,3 Nm	Bearing frictional torque
CaL	1200 N/μm	Axial rigidity
ckL	750 Nm/mrad	Tilting rigidity
M <sub>m</sub>	5,5 kg x cm <sup>2</sup>	Mass moment of inertia for rotating inner ring
	2,5 μm	Axial runout The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	12	Quantity of fixing screws to DIN 912-10.9 Screws not included in delivery.
	M8	Size of fixing screws to DIN 912-10.9 Tightening torque of fixing screws according to manufacturer's data. Screws not included in delivery.
	ZMA40/62	Designation of recommended INA locknut
	AM40	Designation of recommended INA locknut Locknuts not included in delivery.
MA	110 Nm	Tightening torque Only valid in conjunction with INA precision locknuts
	25185 N	Axial preload force





