



Rod ends GIR45-DO-2RS (Series GIR..-DO-2RS)

with internal thread, requiring maintenance, to DIN ISO 12 240-4, lip seals on both sides, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	45 mm	Tolerance: 0 / -0,012
d2	102 mm	
l4	196 mm	
	0,043 - 0,12 mm	Radial internal clearance CN
B	32 mm	Tolerance: 0 / -0,12
C1	27 mm	
D	68 mm	
d1	50,7 mm	
d3	M42X3	Thread runout or thread groove at manufacturer's discretion
d4	58 mm	
d5	70 mm	
dk	60 mm	
h1	145 mm	
l3	65 mm	
l5	20 mm	
l7	52 mm	
r1s min	0,6 mm	Chamfer dimension
W	60 mm	
α	7 °	
m	2,5 kg	Mass
C _r	128000 N	Basic dynamic load rating, radial
C _{0r}	259000 N	Basic static load rating, radial

Basic load rating of housing

