



# Axial angular contact ball bearings

## ZKLF2068-2RS (Series ZKLF..-2RS)

double direction, for screw mounting, lip seals on both sides

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	20 mm	Tolerance: -0,005
D	68 mm	Tolerance: -0,01
B	28 mm	Tolerance: -0,25
	M6	Threaded connector for lubrication
	60 °	Contact angle
1)		Extraction slot
b	3 mm	
d1	34,5 mm	
d2	6,8 mm	
Da	43 mm	
max		
da	25 mm	
min		
l	19 mm	
J	53 mm	
r1	0,6 mm	
min		
rmin	0,3 mm	
t	4 X 90°	Pitch t Quantity X t
m	0,61 kg	Mass
Ca	26000 N	Basic dynamic load rating, axial
C0a	47000 N	Basic static load rating, axial
nG	3000 1/min	Limiting speed for grease lubrication
Fett		

MRL	0,3 Nm	Bearing frictional torque
CaL	650 N/μm	Axial rigidity
ckL	140 Nm/mrad	Tilting rigidity
Mm	0,273 kg x cm <sup>2</sup>	Mass moment of inertia for rotating inner ring
	2 μm	Axial runout
		The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	4	Quantity of fixing screws to DIN 912-10.9 Screws not included in delivery.
	M6	Size of fixing screws to DIN 912-10.9 Tightening torque of fixing screws according to manufacturer's data. Screws not included in delivery.
	ZM20	Designation of recommended INA locknut
	AM20	Designation of recommended INA locknut Locknuts not included in delivery.
MA	18 Nm	Tightening torque Only valid in conjunction with INA precision locknuts
	9079 N	Axial preload force





