



Needle roller/axial cylindrical roller bearings ZARF50115-TV (Series ZARF)

double direction, for screw mounting

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	50 mm	
D	115 mm	
H	60 mm	
6)		Mounting dimension for seal carrier assembly DRS. Seal carriers: see under "Accessories".
B	11,5 mm	
C	22,5 mm	
C ₁	12,5 mm	
D ₁	78 mm	
d ₁	6 mm	
D _a max	79 mm	Mounting dimensions If rotary shaft seals are used, the outside diameter of the sealing ring must be taken into consideration.
d _a min	67 mm	Mounting dimensions If rotary shaft seals are used, the outside diameter of the sealing ring must be taken into consideration.
H ₁	40 mm	
J	94 mm	
r ₁ min	0,6 mm	
r _{min}	0,3 mm	
m	2,1 kg	Mass
C _a	90000 N	Basic dynamic load rating, axial
C _{0a}	300000 N	Basic static load rating, axial



Cr	40000 N	Basic dynamic load rating, radial
Cor	82000 N	Basic static load rating, radial
nG	3600 1/min	Limiting speed for oil lubrication (valid only with adequate oil cooling)
Öl		
nG	1200 1/min	Limiting speed for grease lubrication
Fett		
MRL	2,2 Nm	Bearing frictional torque
CaL	4800 N/µm	Axial rigidity
ckL	2470 Nm/mrad	Tilting rigidity
Mm	8,42 kg x cm ²	Mass moment of inertia for rotating inner ring
	1 µm	Axial runout The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	12	Quantity of fixing screws to DIN 912-10.9 Screws not included in delivery.
	M8	Size of fixing screws to DIN 912-10.9 Tightening torque of fixing screws according to manufacturer's data. Screws not included in delivery.
	ZMA50/75	Designation of recommended INA locknut
	AM50	Designation of recommended INA locknut
MA	85 Nm	Tightening torque Only valid in conjunction with INA precision locknuts
	18410 N	Axial preload force Locknuts and fixing screws not included in delivery.



