



Rod ends GIL12-DO (Series GIL..-DO)

with internal thread, requiring maintenance, to DIN ISO 12 240-4, left hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	12 mm	Tolerance: 0 / -0,008
d2	34 mm	
l4	67 mm	
	0,023 - 0,068 mm	Radial internal clearance CN
B	10 mm	Tolerance: 0 / -0,12
C1	8 mm	
D	22 mm	
d1	14,9 mm	
d3	M12	
d4	17,5 mm	
d5	22 mm	
dk	18 mm	
h1	50 mm	
l3	23 mm	
l5	6,5 mm	
l7	18 mm	
r1s min	0,3 mm	Chamfer dimension
W	19 mm	
α	11 °	
		Without relubrication facility
m	0,096 kg	Mass
Cr	10800 N	Basic dynamic load rating, radial

Cor 30400 N Basic static load rating, radial
Basic load rating of housing

