



Plummer block housing units

PASE5/8 (Series PASE)

cast iron housing, radial insert ball bearing with eccentric
locking collar to ABMA 15 - 1991, ABMA 14 - 1991,
ISO3228, P seals, inch sizes

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	5/8 inch
d	15,9 mm
L	4,921 inch
L	125 mm
H ₂	2,283 inch
H ₂	58 mm
A	1,260 inch
A ₁	0,748 inch
B ₁	1,126 inch
d ₃	1,102 inch
H	1,189 inch
H ₁	0,551 inch
J	3,622 inch
N	0,433 inch
N ₁	0,433 inch
Q	1/4-28 UNF
S ₁	0,870 inch
m	1,12 lbs Mass
Cr	2200 lbf Basic dynamic load rating, radial
Cr	9600 N Basic dynamic load rating, radial
C _{0r}	1070 lbf Basic static load rating, radial
C _{0r}	4750 N Basic static load rating, radial

GG.ASE03 Designation of housing

GRA010-NPP-B-AS2/V Designation of bearing

