



Rod ends GIKL8-PW (Series GIKL..-PW)

with internal thread, maintenance-free, to DIN ISO 12240-4, left hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	8 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,015 / 0
d2	24 mm	
l4	48 mm	
	0 - 0,035 mm	Radial internal clearance
B	12 mm	Tolerance: 0 / -0,12
C1	9 mm	
D	19 mm	
d1	10,3 mm	
d3	M8	
d4	12,5 mm	
d5	16 mm	
dk	15,875 mm	
h1	36 mm	
l3	16 mm	
l5	5 mm	
l7	13 mm	
r1s min	0,3 mm	Chamfer dimension
W	14 mm	
α	14 °	
		Also corresponds to ISO 8 139
m	0,047 kg	Mass
Cr	12900 N	Basic dynamic load rating, radial

Cor 13100 N Basic static load rating, radial
Basic load rating of housing

