



Rod ends GIKR6-PB (Series GIKR..-PB)

with internal thread, requiring maintenance, to DIN ISO 12240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	6 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,012 / 0
d2	20 mm	
l4	40 mm	
	0 - 0,035 mm	Radial internal clearance Deviation from DIN 12240-1, dimension series K
B	9 mm	Tolerance: 0 / -0,12
C1	6,75 mm	
D	16 mm	
d1	8,9 mm	
d3	M6	
d4	10 mm	
d5	13 mm	
dk	12,7 mm	
h1	30 mm	
l3	12 mm	
l5	5 mm	
l7	11 mm	
r1s min	0,3 mm	Chamfer dimension
W	11 mm	
α	13 °	
m	0,022 kg	Mass
Cr	4320 N	Basic dynamic load rating, radial

Cor

7990 N Basic static load rating, radial
Basic load rating of housing

