



Rod ends GIKR25-PW (Series GIKR..-PW)

with internal thread, maintenance-free, to DIN ISO 12240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	25 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,021 / 0
d2	60 mm	
l4	124 mm	
	0 - 0,035 mm	Radial internal clearance
B	31 mm	Tolerance: 0 / -0,12
C1	22 mm	
D	47 mm	
d1	29,5 mm	
d3	M24X2	
d4	33,5 mm	
d5	42 mm	
dk	42,85 mm	
h1	94 mm	
l3	42 mm	
l5	12 mm	
l7	32 mm	
r1s min	0,3 mm	Chamfer dimension
W	36 mm	
α	15 °	
		Also corresponds to ISO 8139
m	0,73 kg	Mass
Cr	84800 N	Basic dynamic load rating, radial

Cor 72900 N Basic static load rating, radial
Basic load rating of housing

