



# Angular contact ball bearings

## 7202-B-2RS-TVP (Series 72..-B-2RS)



main dimensions to DIN 628-1, contact angle  $\alpha = 40^\circ$ , lip seals on both sides

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue selection system (<http://www.fag.de/content.fag.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	15 mm
D	35 mm
B	11 mm
a	16 mm
D <sub>2</sub>	29,3 mm
d <sub>2</sub>	19,7 mm
D <sub>3</sub>	32,3 mm
D <sub>a</sub> max	30,8 mm
d <sub>a</sub> min	19,2 mm
D <sub>b</sub> max	32,6 mm
r <sub>1</sub> min	0,3 mm
r <sub>a1</sub> max	0,3 mm
r <sub>a</sub> max	0,6 mm
r <sub>min</sub>	0,6 mm
$\alpha$	40 ° Contact angle
m	0,048 kg Mass
C <sub>r</sub>	8400 N Basic dynamic load rating, radial

Cor	4450 N	Basic static load rating, radial
nc	24000 1/min	Limiting speed
nb	- 1/min	Reference speed
Cur	300 N	Fatigue limit load, radial

