



Rod ends GIR10-DO (Series GIR..-DO)

with internal thread, requiring maintenance, to DIN ISO 12 240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	10 mm	Tolerance: 0 / -0,008
d2	29 mm	
l4	57,5 mm	
	0,023 - 0,068 mm	Radial internal clearance CN
B	9 mm	Tolerance: 0 / -0,12
C1	7 mm	
D	19 mm	
d1	13,2 mm	
d3	M10	
d4	15 mm	
d5	19 mm	
dk	16 mm	
h1	43 mm	
l3	20 mm	
l5	6,5 mm	
l7	15 mm	
r1s min	0,3 mm	Chamfer dimension
W	17 mm	
α	12 °	
		Without relubrication facility
m	0,061 kg	Mass
Cr	8160 N	Basic dynamic load rating, radial

Cor	22000 N Basic static load rating, radial Basic load rating of housing
-----	--

