



Rod ends GIKR20-PW (Series GIKR..-PW)

with internal thread, maintenance-free, to DIN ISO 12240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	20 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,021 / 0
d2	50 mm	
l4	102 mm	
	0 - 0,035 mm	Radial internal clearance
B	25 mm	Tolerance: 0 / -0,12
C1	18 mm	
D	40 mm	
d1	24,3 mm	
d3	M20X1,5	
d4	27,5 mm	
d5	35 mm	
dk	34,925 mm	
h1	77 mm	
l3	33 mm	
l5	10 mm	
l7	26 mm	
r1s min	0,3 mm	Chamfer dimension
W	30 mm	
α	14 °	
		Also corresponds to ISO 8139
m	0,42 kg	Mass
Cr	56600 N	Basic dynamic load rating, radial

Cor 45600 N Basic static load rating, radial
Basic load rating of housing

