



Rod ends GIR6-DO (Series GIR..-DO)

with internal thread, requiring maintenance, to DIN ISO 12 240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	6 mm	Tolerance: 0 / -0,008
d2	21 mm	
l4	40,5 mm	
	0,023 - 0,068 mm	Radial internal clearance CN
B	6 mm	Tolerance: 0 / -0,12
C1	4,4 mm	
D	14 mm	
d1	8 mm	
d3	M6	
d4	10 mm	
d5	13 mm	
dk	10 mm	
h1	30 mm	
l3	11 mm	
l5	5 mm	
l7	12 mm	
r1s min	0,3 mm	Chamfer dimension
W	11 mm	
α	13 °	
		Without relubrication facility
m	0,021 kg	Mass
Cr	3400 N	Basic dynamic load rating, radial

Cor 10300 N Basic static load rating, radial
Basic load rating of housing

