



# Rod ends GIKL25-PB (Series GIKL..-PB)

with internal thread, requiring maintenance, to DIN ISO 12240-4, left hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	25 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,021 / 0
d2	60 mm	
l4	124 mm	
	0 - 0,035 mm	Radial internal clearance Deviation from DIN 12240-1, dimension series K
B	31 mm	Tolerance: 0 / -0,12
C1	22 mm	
D	47 mm	
d1	29,5 mm	
d3	M24X2	
d4	33,5 mm	
d5	42 mm	
dk	42,85 mm	
h1	94 mm	
l3	42 mm	
l5	12 mm	
l7	32 mm	
r1s min	0,3 mm	Chamfer dimension
W	36 mm	
α	15 °	
m	0,73 kg	Mass
Cr	47100 N	Basic dynamic load rating, radial

Cor 72900 N Basic static load rating, radial  
Basic load rating of housing

