



## Rod ends GIKL30-PW (Series GIKL..-PW)

with internal thread, maintenance-free, to DIN ISO 12240-4, left hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	30 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,021 / 0
d2	70 mm	
l4	145 mm	
	0 - 0,035 mm	Radial internal clearance
B	37 mm	Tolerance: 0 / -0,12
C1	25 mm	
D	55 mm	
d1	34,8 mm	
d3	M30X2	
d4	40 mm	
d5	50 mm	
dk	50,8 mm	
h1	110 mm	
l3	51 mm	
l5	15 mm	
l7	37 mm	
r1s min	0,3 mm	Chamfer dimension
W	41 mm	
$\alpha$	17 °	
m	1,1 kg	Mass
C <sub>r</sub>	114000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	95900 N	Basic static load rating, radial

Basic load rating of housing

