



Rod ends GIKR14-PB (Series GIKR..-PB)

with internal thread, requiring maintenance, to DIN ISO 12240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	14 mm	Bore tolerance: H7 (arithmetic mean value) Tolerance: +0,018 / 0
d2	36 mm	
l4	75 mm	
	0 - 0,035 mm	Radial internal clearance Deviation from DIN 12240-1, dimension series K
B	19 mm	Tolerance: 0 / -0,12
C1	13,5 mm	
D	28 mm	Deviation from DIN 12240-4, dimension series K
d1	16,8 mm	
d3	M14	
d4	21 mm	
d5	26 mm	
dk	25,4 mm	
h1	57 mm	
l3	25 mm	
l5	8 mm	
l7	18 mm	
r1s min	0,3 mm	Chamfer dimension
W	22 mm	
α	16 °	
m	0,16 kg	Mass
Cr	17100 N	Basic dynamic load rating, radial

Cor	32000 N Basic static load rating, radial Basic load rating of housing
-----	--

