



Needle roller/axial cylindrical roller bearings ZARN60120-TV (Series ZARN)

double direction

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system (<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	60 mm
D	120 mm
H	82 mm
B	17,5 mm
C	25 mm
D ₁	105 mm
D _a max	106 mm Mounting dimensions If rotary shaft seals are used, the outside diameter of the sealing ring must be taken into consideration.
d _a min	90 mm Mounting dimensions If rotary shaft seals are used, the outside diameter of the sealing ring must be taken into consideration.
H ₁	53,5 mm
r ₁ min	0,6 mm
r _{min}	0,3 mm
m	3,7 kg Mass
C _a	187000 N Basic dynamic load rating, axial
C _{0a}	550000 N Basic static load rating, axial
C _r	44500 N Basic dynamic load rating, radial
C _{0r}	92000 N Basic static load rating, radial
n _G 0i	2700 1/min Limiting speed for oil lubrication (valid only with adequate oil cooling)
n _G	950 1/min Limiting speed for grease lubrication

Fett	
MR _L	4,2 Nm Bearing frictional torque
Ca _L	5300 N/μm Axial rigidity
Ck _L	4300 Nm/mrad Tilting rigidity
M _m	43,8 kg x cm ² Mass moment of inertia for rotating inner ring
	1 μm Axial runout
	The axial runout data for screw drive bearing arrangements are based on the rotating inner ring.
	ZMA60/98 Designation of recommended INA locknut
	AM60 Designation of recommended INA locknut
MA	250 Nm Tightening torque
	Only valid in conjunction with INA precision locknuts
	42190 N Axial preload force
	Locknuts not included in delivery.



