



Rod ends GIR15-DO (Series GIR..-DO)

with internal thread, requiring maintenance, to DIN ISO 12240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	15 mm	Tolerance: 0 / -0,008
d2	40 mm	
l4	81 mm	
	0,03 - 0,082 mm	Radial internal clearance CN
B	12 mm	Tolerance: 0 / -0,12
C1	10 mm	
D	26 mm	
d1	18,4 mm	
d3	M14	
d4	21 mm	
d5	26 mm	
dk	22 mm	
h1	61 mm	
l3	30 mm	
l5	8 mm	
l7	20 mm	
r1s min	0,3 mm	Chamfer dimension
W	22 mm	
α	8 °	
		Relubrication via lubrication hole in housing
m	0,18 kg	Mass
Cr	16900 N	Basic dynamic load rating, radial

Cor

44800 N Basic static load rating, radial
Basic load rating of housing

