


**FAG****NN3048-AS-K-M-SP**

Cylindrical roller bearing

Super precision cylindrical roller bearings
NN30...-AS-K-M-SP, non-locating bearing,
double row, with tapered bore, taper 1:12,
separable, with cage

Materiálové číslo Schaeffler:
0192315980000

Technické informace



Vaše aktuální varianta produktu

Cage	M	Brass Cage
Tolerance class	SP	Tolerance class SP
Bore type	K	Tapered, taper 1:12
Change mark	A	Internal Variant A
Radial internal clearance	C1 (Group 1)	Internal clearance smaller than C2
Number of rolling element rows	2	Double-row design

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	360 mm	Outside diameter
B	92 mm	Width
C _r	840.000 N	Basic dynamic load rating, radial
C _{0r}	1.580.000 N	Basic static load rating, radial
C _{ur}	177.000 N	Fatigue load limit, radial
n _{G Grease}	2.170 1/min	Limiting speed for grease lubrication
n _{G Oil}	2.550 1/min	Limiting speed for oil lubrication
≈m	30,8 kg	Hmotnost



Mounting dimensions

d _a	274 mm	Diameter shaft shoulder
h12		Diameter shaft shoulder tolerance
D _a	337 mm	Diameter of housing shoulder
H12		Shoulder diameter outer ring clearance
r _{a1} max	2,5 mm	Maximum recess radius

Dimensions

r ₁ min	3 mm	Minimum chamfer dimension
E	330 mm	Raceway diameter outer ring
n _s	15 mm	Width of lubricating groove
d _s	8 mm	Diameter lubrication hole
s	6,1 mm	Axial displacement

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	150 °C	Operating temperature max.

Vlastnosti

	Radiální zatížení
	Mazání (plastickým) mazivem
	Mazání olejem
	Neutěsněné
	Velké ložisko