



Axial angular contact ball bearings

ZKLF2575-2RS (Series ZKLF..-2RS)

double direction, for screw mounting, lip seals on both sides

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	25 mm	Tolerance: -0,005
D	75 mm	Tolerance: -0,01
B	28 mm	Tolerance: -0,25
	M6	Threaded connector for lubrication
	60 °	Contact angle
1)		Extraction slot
b	3 mm	
d ₁	40,5 mm	
d ₂	6,8 mm	
D _a max	48 mm	
d _a min	32 mm	
l	19 mm	
J	58 mm	
r ₁ min	0,6 mm	
r _{min}	0,3 mm	
t	4 X 90°	Pitch t Quantity X t
m	0,72 kg	Mass
C _a	27500 N	Basic dynamic load rating, axial
C _{0a}	55000 N	Basic static load rating, axial
n _G Fett	2600 1/min	Limiting speed for grease lubrication



