



# Rod ends GIR25-DO (Series GIR..-DO)

with internal thread, requiring maintenance, to DIN ISO 12240-4, right hand thread

The datasheet is only an overview of dimensions and basic load ratings of the selected product. Please always observe all the guidelines in these overview pages. Further information is given on many products under the menu item "Description". You can also order comprehensive information via the Catalogue ordering system

(<http://www.ina.de/content.ina.de/en/mediathek/library/library.jsp>) or by telephone on +49 (91 32) 82 - 28 97.

d	25 mm	Tolerance: 0 / -0,01
d2	64 mm	
l4	126 mm	
	0,037 - 0,1 mm	Radial internal clearance CN
B	20 mm	Tolerance: 0 / -0,12
C1	17 mm	
D	42 mm	
d1	29,3 mm	
d3	M24X2	
d4	33,5 mm	
d5	42 mm	
dk	35,5 mm	
h1	94 mm	
l3	48 mm	
l5	12 mm	
l7	32 mm	
r1s min	0,6 mm	Chamfer dimension
W	36 mm	
$\alpha$	7 °	
m	0,64 kg	Mass
C <sub>r</sub>	48300 N	Basic dynamic load rating, radial
C <sub>0r</sub>	88300 N	Basic static load rating, radial

Basic load rating of housing

